

# Faceal Wetlook –S (shiny)



**WATER REPELLENT – OIL REPELLENT ACRYLIC WAX  
FOR COMPLETE FLOORING PROTECTION WITH A SEMI GLOSS ‘WET LOOK’**

## PRODUCT DESCRIPTION

**FACEAL WETLOOK** is an all-in product offering both water and oil repellency protection to all porous building materials, and is particularly suited for flooring.

**FACEAL WETLOOK** can be used inside and outside on all porous materials such as natural stone, concrete, terracotta, cement and self-locking paving.

**FACEAL WETLOOK** is an environmentally friendly, completely water-borne product that is non-toxic and does not contain solvents or silicone. It is designed to protect all porous materials from water and oil penetration and all types of staining.

**FACEAL WETLOOK** is an impregnating acrylic wax that leaves the treated surface permeable to both air and water vapour.

**FACEAL WETLOOK** delivers a gloss/satin ‘wet look’ to the treated surface, as well as bringing up the true colour. It is also UV-resistant and does not discolor with time.

A surface treated with **FACEAL WETLOOK** is easier to care for and will be protected against the main causes of deterioration such as atmospheric pollution, grease-based stains and penetration by liquids.

## CHEMICAL COMPOSITION

- Very high quality, solvent and silicone-free acrylic protective wax finish

## ADVANTAGES AND CHARACTERISTICS

- Can be applied to vertical, horizontal, inside and outside surfaces
- Prevents the penetration of water and oily liquids
- Anti-staining, anti-dirt. Prevents chewing-gum from sticking to treated surfaces and stops dirt due to pollution from building up again. Limits moss and lichen growth.
- Prevents deterioration resulting from the freeze-thaw cycle
- Makes cleaning easier
- Non film-forming, allows the surface to breathe
- Non-hazardous and non-toxic
- Water-borne product
- Solvent and silicone-free
- 95% + biodegradable
- UV-resistant, does not discolour
- Ready to use
- Easy to use
- Non-flammable

## PACKAGING

10 and 25 litre containers

## TECHNICAL DATA

Physical State at 20 °C	: Liquid
Appearance	: Milky
Odour	: None
pH	: 7 ± 0.5
Boiling point [°C]	: 100 °C
Density	: 1.0 Kg/L
Solubility in water [vol/vol]	: Fully soluble
Flash Point [°C]	: Not applicable

## APPLICATION

- Shake the container well before using
- Apply the product to the surface only after it has been cleaned, dusted and dried
- Use neat, do not dilute
- Apply using a wet mop or a roller
- The treated surface should be impregnated to saturation point, and two applications should be applied. Time interval between applications: 30 minutes
- To accentuate the 'wet look' you may add a third application after leaving to dry for an hour
- Do not over-apply the product, remove any excess
- Drying time before traffic or people are allowed back onto treated surface:  
24 hours
- For the optimum performance: wait 5 to 7 days

## COVERAGE PER LITRE

Coverage depends on the porosity of the material. The figures below are approximate and should be used only as a general guideline:

**6 - 10 m<sup>2</sup> / litre**

## CLEANING EQUIPMENT

- Immediately after you have finished clean the tools and equipment used with water

## STORAGE

- Keep in a cool, dry place
- Keep away from extreme cold, do not store in conditions below 5°C

## RECOMMENDATIONS

- Remove all atmospheric pollution-related dirt from all surfaces to be treated before starting the treatment.
- To obtain the best look and results on application, **FACEAL WETLOOK** should be shaken before use and must be used only when the temperature of the surfaces to be treated is greater than 5°C
- Do not apply during rainy or very hot weather
- Do not dilute or mix with any other product

## HEALTH AND SAFETY

- Respiratory Protection: Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.
- Hand Protection: None required
- Skin Protection: No special protective clothing or skin protection is required under normal conditions of use
- Eye Protection: If there is a real risk of splashing, wear protective goggles
- If swallowed: do not induce vomiting. Contact a doctor or a specialist

**KEEP OUT OF THE REACH OF CHILDREN**

## TECHNICAL ASSISTANCE

### PSS INTERSERVICE AG

Poststr. 1, POB 315, CH-8954 Geroldswil, Switzerland

Tél: +41-44-749 24 24 • Fax : +41-44-749 24 25

E-mail : [info@pss-technology.com](mailto:info@pss-technology.com) • [www.pss-technology.com](http://www.pss-technology.com)

**Important:** The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use in individual cases. For more information, please see the Material safety data sheet.